BEHR PREMIUM® Transparent Weatherproofing All-In-One Wood Finish

- For Decks, Fences & Siding
- Penetrating Advanced 100% Acrylic
- Enhanced UV Protection
- Mildew Resistant Finish
- Easy Water Clean-Up

Must Prep Before Applying Wood Finish

2 Thin Coats Required

Spread Rate:
1st **Coat** 300-350 Sq. Ft.
2nd **Coat** 600-700 Sq. Ft.

Soap & Water Clean-Up

CAUTION: Finished surfaces may become slippery when wet.

WHERE TO USE

"For Wood Substrates Only" Recommended for properly prepared new to slightly weathered, unsealed exterior wood surfaces (0-5 years exposure) such as: Decks, Railings, Shakes, Shingles, Siding, Roofs, Fences and Wood Patio Furniture.

PREPARATION †

(The following steps and products are required.) Use a product such as BEHR PREMIUM® NO. 64 Wood Stain & Finish Stripper to remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood. BEHR PREMIUM NO. 63 All-In-One Wood Cleaner **MUST** be used following NO. 64 to clean, brighten & neutralize wood. When NO. 64 is not needed, use a product such as NO. 63 to clean and brighten the wood surface and to remove light to medium exterior stains caused by mold, mildew, algae & fungus. On new wood, use a product such as NO. 63 to remove mill glaze and open the pores of the wood. Rinse thoroughly and allow to dry before coating. Lightly sand to remove remaining wood fibers/fuzz.

APPLICATION

(For best results, a pad applicator is recommended over large deck areas.) Must applybetween 40-90˚ F (4.5-32˚ C). Do not use if rain is expected within 24 hours. The wood surface must be completely dry before application. Intermix multiple containers to ensure color uniformity. DO NOT THIN PRODUCT. Stir product occasionally throughout application. Test product for penetration and color on a small hidden area before proceeding. Use a nylon/polyester brush for areas requiring more accuracy. Use of rollers should be limited to rough surfaces only. Use 3/8" nap or longer when appropriate. A high quality pump sprayer with a variable tip or an airless sprayer with a .015 - .019" tip may be used. Work in small sections lightly saturating the surface and immediately back-brush or use pad applicator to eliminate puddling, remove excess and evenly distribute the finish. Maintain a wet edge when applying. Apply product end-to-end or to board lengths to prevent lap marks. Over application of finish will lead to surface failure including peeling and cracking. **Avoid applying finish too heavily. Two thin coats required.** For optimum performance, coat all six sides of wood.

WARRANTY

- Visit www.Behr.com for complete warranty information.

DRY TIME

1-2 hours before recoat. Allow 72 hours for full cure.

DISPOSAL

For disposal of empty containers and unused product contact your household refuse collection service.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2013 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <275 g/L • REV. 3/13